


m o o o i

Coppélia Suspended

ARIHIRO MIYAKE



Coppélia comes to life in a whirl of flowing motion and sparkling light. With a graceful sense of wonder, a beautiful mechanical doll appears to magically come to life in the famous ballet Coppélia. In the performance the ballerina traces, with sinuous movements, a delicate after-image in the air, which inspires the fluid motion in the design of Miyake's Coppélia Suspended Lamp. The graceful dance, staged by the three-dimensionally crossed wire structure, leads the spectator to dozens of glowing LED lights, which define the contour and the magical glow of Miyake's interpretation of a classic chandelier.

Detailing



A technical masterpiece comparable to a high-class ballet. A double structure forms a thin and open shape that transports the electric current.

Colours



Black

Chrome

Coppélia Suspended / Large

Dimensions

101cm | 39.8"



Product

WIDTH 101cm | 39.8"

HEIGHT 54cm | 21.3"

DEPTH 101cm | 39.8"

DIAMETER 101cm | 39.8"

WEIGHT NETTO 3kg | 6.61lbs

Packaging

WIDTH 111cm | 43.7"

HEIGHT 63cm | 24.8"

CUBAGE 0.78m³ | 27.41ft³

LENGTH 111cm | 43.7"

WEIGHT 14kg | 30.86lbs

Technical CCC

MATERIAL

Stainless steel frame with polycarbonate shades and suspension bracket

ENERGY LABEL

B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

54

SHAPE

Round

DIAMETER SHADE

100cm | 39.4"

INPUT VOLTAGE

200-265V

FREQUENCY

50/60

MAX POWER CONSUMPTION

33W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Transparent with tinned cores

CABLE LENGTH

400cm | 157.5"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CHROM X

0.4487

CHROM Y

0.3945

COLOUR TEMPERATURE

2700 K (max)

CRI

88

LIGHT DIRECTION

All directions

LIGHT OUTPUT

676 lm

R9

40

DIMMING & LIGHTING CONTROL

1-10V, Mains, Leading edge, Forward phase, Mains,
Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

Technical CE

MATERIAL

Stainless steel frame with polycarbonate shades and suspension bracket

ENERGY LABEL

B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

54

SHAPE

Round

DIAMETER SHADE

100cm | 39.4"

INPUT VOLTAGE

200-265V

FREQUENCY

50/60

MAX POWER CONSUMPTION

33W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Transparent with tinned cores

CABLE LENGTH

400cm | 157.5"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CHROM X

0.4487

CHROM Y

0.3945

COLOUR TEMPERATURE

2700 K (max)

CRI

88

LIGHT DIRECTION

All directions

LIGHT OUTPUT

676 lm

R9

40

DIMMING & LIGHTING CONTROL

1-10V, Mains, Leading edge, Forward phase, Mains,
Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



Technical UL

MATERIAL

Stainless steel frame with polycarbonate shades and suspension bracket

ENERGY LABEL

B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

54

SHAPE

Round

DIAMETER SHADE

100cm | 39.4"

INPUT VOLTAGE

100-127V

FREQUENCY

50/60

MAX POWER CONSUMPTION

33W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Transparent with tinned cores

CABLE LENGTH

400cm | 157.5"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CHROM X

0.4487

CHROM Y

0.3945

COLOUR TEMPERATURE

2700 K (max)

CRI

88

LIGHT DIRECTION

All directions

LIGHT OUTPUT

676 lm

R9

40

DIMMING & LIGHTING CONTROL

1-10V, Mains, Leading edge, Forward phase, Mains, Trailing edge, Reverse phase


See last page for more information about the dimming possibilities.



Coppélia Suspended / Small

Dimensions

68cm | 26.7"



Product

WIDTH 68cm | 26.8"

HEIGHT 42.5cm | 16.7"

DEPTH 68cm | 26.8"

DIAMETER 68cm | 26.8"

WEIGHT NETTO 1.8kg | 3.97lbs

Packaging

WIDTH 79cm | 31.1"

HEIGHT 50cm | 19.7"

CUBAGE 0.31m³ | 11.02ft³

LENGTH 79cm | 31.1"

WEIGHT 9kg | 19.84lbs

Technical CCC

MATERIAL

Stainless steel frame with polycarbonate shades and suspension bracket

ENERGY LABEL

B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

36

SHAPE

Round

DIAMETER SHADE

69cm | 27.2"

INPUT VOLTAGE

200-265V

FREQUENCY

50/60

MAX POWER CONSUMPTION

22W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Transparent with tinned cores

CABLE LENGTH

400cm | 157.5"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CHROM X

0.4487

CHROM Y

0.3945

COLOUR TEMPERATURE

2700 K (max)

CRI

88

LIGHT DIRECTION

All directions

LIGHT OUTPUT

450 lm

R9

40

DIMMING & LIGHTING CONTROL

1-10V, Mains, Leading edge, Forward phase, Mains,
Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

Technical CE

MATERIAL

Stainless steel frame with polycarbonate shades and suspension bracket

ENERGY LABEL

B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

36

SHAPE

Round

DIAMETER SHADE

69cm | 27.2"

INPUT VOLTAGE

200-265V

FREQUENCY

50/60

MAX POWER CONSUMPTION

22W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Transparent with tinned cores

CABLE LENGTH

400cm | 157.5"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CHROM X

0.4487

CHROM Y

0.3945

COLOUR TEMPERATURE

2700 K (max)

CRI

88

LIGHT DIRECTION

All directions

LIGHT OUTPUT

450 lm

R9

40

DIMMING & LIGHTING CONTROL

1-10V, Mains, Leading edge, Forward phase, Mains,
Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



Technical UL

MATERIAL

Stainless steel frame with polycarbonate shades and suspension bracket

ENERGY LABEL

B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

36

SHAPE

Round

DIAMETER SHADE

69cm | 27.2"

INPUT VOLTAGE

100-127V

FREQUENCY

50/60

MAX POWER CONSUMPTION

22W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Transparent with tinned cores

CABLE LENGTH

400cm | 157.5"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CHROM X

0.4487

CHROM Y

0.3945

COLOUR TEMPERATURE

2700 K (max)

CRI

88

LIGHT DIRECTION

All directions

LIGHT OUTPUT

450 lm

R9

40

DIMMING & LIGHTING CONTROL

1-10V, Mains, Leading edge, Forward phase, Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



Dimming & Lighting Control

1-10V

The luminaire is dimmable by using an either internally mounted or externally placed 1-10V dimmer switch. 1-10V is a dimming system widely used in some parts of the world, for example in North-America. This method will need its own wiring. Dimming quality is perfect, without flicker, the range can be limited and the luminaire cannot be dimmed to off. To turn off the luminaire a switch is needed.

Compatible models: Large CE, Large UL, Small CE, Small UL

Mains, Leading edge, Forward phase

Control the mood with ease. This light fixture can be dimmed using an external Electronic Low Voltage dimmer. Simply connect it to an existing outlet—no need to rewire your home. Choose a dimmer designed for LED lights, suitable for 5 watts or lower, and supporting a L-type (inductive load). This ensures compatibility and smooth operation. As with all delicate lighting, the experience of dimming may occasionally bring a flicker, hum, or soft buzz.

Compatible models: Large CE, Large UL, Small CE, Small UL

Mains, Trailing edge, Reverse phase

Control the mood with ease. This light fixture can be dimmed using an external Electronic Low Voltage dimmer. Simply connect it to an existing outlet—no need to rewire your home. Choose a dimmer designed for LED lights, suitable for 5 watts or lower, and supporting a C-type (capacitive load). This ensures compatibility and smooth operation. As with all delicate lighting, the experience of dimming may occasionally bring a flicker, hum, or soft buzz.

Compatible models: Large CE, Large UL, Small CE, Small UL
